

# REDI-FLANGE™

# UNITED

**No Welding!  
No Threading!**



ANSI B16.1 Class 125  
ANSI B16.5 Class 150



## STANDARDS:

Ductile Iron - ASTM A536  
Grade 65-45-12. Drilling to  
ANSI B16.1 - 125 lb.  
ANSI B16.5 - 150 lb.

**SET SCREW:** AISI 4140 steel  
Tensile 160,000 psi minimum

**GASKET:** SBR (BUNA-N).

## HYDROSTATIC TEST PRESSURE:

MODEL - RFC-2/RFS-2 - 125 lb./150 lb.  
2 in. - 8 in. 600 psi (UL rated 175 psi)  
10 in. - 12 in. 525 psi (UL rated 175 psi)

MODEL - RFC-4 - 125 lb./150 lb.

3 in. - 12 in. 750 psi (UL rated 175 psi)  
14 in. - 24 in. 450 psi  
30 in. - 36 in. 300 psi  
42 in. - 48 in. 150 psi

The *Redi-Flange* joins valves, fittings and equipment with integral flanged ends to plain end pipe, without the need of pipe end preparation. Absolutely no threading, welding, or grooving is necessary. The working principle of the *Redi-Flange* is relatively simple. Slide the flange over plain end pipe and follow it with a standard mechanical joint gasket. When the *Redi-Flange* is brought to mate against an existing flange, and the flange bolts are tightened, a compression type seal is created against the mating flange, and pipe surface. End restraint is provided when the set screws are tightened.

Nom. Pipe Size	Part No.	D.I. Pipe O.D. RFC-2-D	Steel Pipe O.D. RFS-2-S	Flange O.D.	Bolt Circle	Bolt Hole Dia.	Set Screws		Wgt. Approx.
							No.	Size	
2	RFC-201	2.50	2.38	6	4-3/4	3/4	2	1/2 x 1	3.5
2-1/2	RFC-202	-	2.88	7	5-1/2	3/4	4	1/2 x 1	4
*3	RFC-203	3.96	3.50	7-1/2	6	3/4	4	1/2 x 1	5
*4	RFC-204	4.80	4.50	9	7-1/2	3/4	4	1/2 x 1	8
5	RFC-205	-	5.56	10	8-1/2	7/8	8	1/2 x 1	9
*6	RFC-206	6.90	6.625	11	9-1/2	7/8	8	1/2 x 1	10
*8	RFC-208	9.05	8.625	13-1/2	11-3/4	7/8	8	5/8 x 1 1/4	17
*10	RFC-210	11.10	10.75	16	14-1/4	1	12	5/8 x 1-1/4	22
12	RFC-212	13.20	12.75	19	17	1	12	5/8 x 1-1/4	31

Use Prefix RFC for DI Pipe - RFS for Steel Pipe

Nom. Pipe Size	Part No.	D.I. Pipe O.D. RFC-4-D	Flange O.D.	Bolt Circle	Bolt Hole Dia.	Set Screws		Wgt. Approx.
						No.	Size	
*3	RFC-403	3.96	7-1/2	6	3/4	4	1/2 x 1	8
*4	RFC-404	4.80	9	7-1/2	3/4	4	1/2 x 1	11
*6	RFC-406	6.90	11	9-1/2	7/8	8	5/8 x 1-1/4	14
*8	RFC-408	9.05	13-1/2	11-3/4	7/8	8	5/8 x 1-1/4	21
*10	RFC-410	11.10	16	14-1/4	1	12	5/8 x 1-1/4	38
12	RFC-412	13.20	19	17	1	12	5/8 x 1-1/4	56
14	RFC-414	15.30	21	18-3/4	1-1/8	12	5/8 x 1-1/4	70
16	RFC-416	17.40	23-1/2	21-1/4	1-1/8	16	5/8 x 1-1/4	79
18	RFC-418	19.50	25	22-3/4	1-1/4	16	3/4 x 2	90
20	RFC-420	21.60	27-1/2	25	1-1/4	20	3/4 x 2	145
24	RFC-424	25.80	32	29-1/2	1-3/8	20	3/4 x 2	175
30	RFC-430	32.00	38-3/4	36	1-3/8	28	1 x 2-1/4	270
36	RFC-436	38.30	46	42-3/4	1-5/8	32	1 x 2-1/4	400
42	RFC-442	44.50	53	49-1/2	1-5/8	36	1 x 2-1/4	495
48	RFC-448	50.80	59-1/2	56	1-5/8	44	1 x 2-1/4	660

\*Denotes UL Listed



**WARNING:** This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**UNITED** Water Products

**United Water Products**  
5355 Ramona Blvd., Jacksonville, FL 32205  
TEL. 877-766-4459 FAX: 877-766-4458  
Website: [www.unitedwaterproducts.com](http://www.unitedwaterproducts.com)